

Rope Dia. (in.)	Rated Capacity - Tons*					
	 Vert.	 Choker Hitch	Basket Hitch			
				 60°	 45°	 30°
<b>6 x 19, 6 x 36</b>						
1/4	0.65	0.48	1.3	1.1	0.91	0.65
5/16	1	0.74	2	1.7	1.4	1
3/8	1.4	1.1	2.9	2.5	2	1.4
7/16	1.9	1.4	3.9	3.4	2.7	1.9
1/2	2.5	1.9	5.1	4.4	3.6	2.5
9/16	3.2	2.4	6.4	5.5	4.5	3.2
5/8	3.9	2.9	7.8	6.8	5.5	3.9
3/4	5.6	4.1	11	9.7	7.9	5.6
7/8	7.6	5.6	15	13	11	7.6
1	9.8	7.2	20	17	14	9.8
1-1/8	12	9.1	24	21	17	12
1-1/4	15	11	30	26	21	15
1-3/8	18	13	36	31	25	18
1-1/2	21	16	42	37	30	21
1-5/8	24	18	49	42	35	24
1-3/4	28	21	57	49	40	28
2	37	28	73	63	52	37
2-1/4	44	35	89	77	63	44
2-1/2	54	42	109	94	77	54
2-3/4	65	51	120	113	92	65
3	77	60	153	133	108	77
3-1/2	102	79	203	176	144	102
4	130	101	260	224	183	130

All capacities in tons of 2,000 lbs. All eye and fitting dimensions in inches.

\*Rated Capacities Basket Hitch based on D/d Ratio of 25.

Rated Capacities based on pin diameter no larger than natural eye width or less than the nominal sling diameter.

Rated Capacities based on design factor of 5.

Horizontal sling angles of less than 30° shall not be used.